

PRO SERIES

FINAL LAP

HARD SURFACE SEAL & FINISH

SELLO SUPERFICIAL DURO/FINAL



Technical Data

Areas of Use

- Terrazzo
- Quarry Tile
- Stone
- Vinyl Tile

Specifications

SSS Item Numbers	48085
Available Sizes	2.5G
Type	Acrylic
Non-volatile solids	18.0±0.5%
Physical State	Liquid
Color	Milky white
Fragrance	Mild
pH	8.5 - 9.0
Dry/Recoat Time	30 minutes
Slip Resistance	56 - .60 (ASTM-D2047-82)
Gloss	Greater than 88
Leveling	Excellent
Sediment	0.1% by volume, max.
Removability	With conventional strippers
Detergent Resistance	Excellent
Viscosity	Water Thin
Stain Resistance	Very good
Chemical Resistance	Good
VOC Content	0.369 lbs./gal.
Storage/Stability	2 years
Freeze/Thaw Stability	Keep from freezing
Weight Per Gallon	8.57 lbs./gal.
Coverage	1000-1500 sq. ft./gal. 1500-2000 sq. ft./gal.

HMIS Hazardous Materials I.D. System

Health	1
Flammability	0
Reactivity	0
Personal Protection	A

What the Pros Know

Don't apply if floor surface temperature is less than 45° F. Powdering will result. Allow extra curing time in humid conditions. Rushing coats will cause recoat disturbance and dulling. Don't overwork finish - just spread evenly and allow to dry. Apply finish only with a clean finish mop - never use a cleaning mop. See label for complete directions and use only as directed.

Description

An extremely durable, long lasting sealer/finish designed especially for terrazzo, quarry tile, brick, stone, Mexican tile, and all other non-resilient floors. Levels and adheres on all the above mentioned surfaces, leaving a durable high quality protective coating that lasts longer than most floor finishes found today.

Directions

Wear safety equipment recommended on MSDS, place Wet Floor Signs and read all directions and cautions prior to beginning your work.



SEALING and FINISHING: Apply a liberal coat of sealer/finish evenly with a clean mop. Allow to dry for at least 30 minutes before applying additional coats. Two or three coats may be desired initially depending on the gloss desired and the condition of the floor.

MAINTENANCE: Use a treated dust mop for the removal of surface dirt and grit. Mop or scrub with a neutral or all-purpose cleaner to remove all soil. After cleaning touch up traffic lanes as necessary or recoat the entire floor. If spray buffing is desired, dust mop floor thoroughly and buff using a spray buff or polishing pad.

This product meets the maximum content requirements for Volatile Organic Compounds (VOCs) as established by state and Federal regulations.

Ideal for Hard Surfaces

Long Lasting

Extremely Durable



MATERIAL SAFETY DATA SHEET

Prepared by: Regulatory Affairs Dept.

(Prepared According to 29 CFR 1910.1200)

N/A=Not Applicable
Effective Date: 5/10 Revision: 6/08

SECTION 1-PRODUCT IDENTIFICATION AND SUPPLIER INFORMATION

Product Name: Final Lap
Generic Name: Hard Surface Seal/Finish
Chemical Family: Acrylic Polymer Blend
Formula: Proprietary
Triple S Product Number: 48085

Manufactured For: Triple S
Address: 2 Executive Park Drive Billerica, MA 01862
Phone #: 800-323-2251

SECTION 2-INGREDIENT INFORMATION

CHEMICAL NAME	CAS NO.	WT. %	PEL	TWA-TLV	STEL-TLV
Water	7732-18-5	to 100			
Acrylic Copolymer Dispersion	63744-68-3	35 to 40			
Ethylene Copolymer	9010-77-9	0 to 5			
Resin Solution	65405-63-2	0 to 5			
Diethylene Glycol Ethyl Ether	111-90-0	0 to 5			

SECTION 3-PHYSICAL DATA

Boiling Point (°F): 212 F.
Vapor Pressure: 20mm Hg @ 68 F.
% Volatile: 80+
Solubility in Water: Complete
Physical Description: Thin milky liquid with characteristic odor.

Specific Gravity: 1.029
Vapor Density (Air=1): >1
pH: 8.5-9.0
Evaporation Rate (Water=1): <1

SECTION 4-FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): N/A
Upper Explosion Limit: N/A
Extinguishing Media: N/A
Special Firefighting Procedures: Non Flammable
Unusual Fire and Explosion Hazards: N/A

SECTION 5-REACTIVITY DATA

Stability: Stable
Hazards Decomposition Products: Will not occur.

Hazardous Polymerization: None
Incompatibility (Materials to Avoid): None

SECTION 6-STORAGE AND HANDLING INFORMATION

Keep out of reach of children. For use by trained personnel only. Keep unauthorized personnel away when applying to floor. Keep container closed during storage. For institutional and industrial use only. Avoid contact with eyes, skin and clothing. Avoid breathing of vapors. Use in well-ventilated area.

SECTION 7-HEALTH HAZARDS AND FIRST AID

Effects of Overexposure:
Skin: Prolonged or repeated contact may cause dermatitis.
Eyes: Eye irritant. May cause redness or swelling.
Inhalation: Vapors may irritate nose, throat and lungs. May cause dizziness, headache, nausea.
Ingestion: May be irritating to the mouth, throat, and gastrointestinal system. Vomiting and diarrhea expected with large doses.
First Aid Procedures:
Skin: Flush with water. Seek medical attention if irritation persists.
Eyes: Flush with large quantities of water, holding eyelids open. Seek medical attention.
Inhalation: Remove victim to fresh air. Seek medical attention if symptoms persist.
Ingestion: Dilute with 2 glasses of water. Seek medical attention if symptoms persist.

SECTION 8-SPECIAL PROTECTION INFORMATION

Respiratory Protection: Use in well-ventilated areas.
Ventilation Requirements: Provide local exhaust to keep TLV of Section 2 ingredients below acceptable limit.
Protective Gloves: Chemical resistant rubber or neoprene.
Eye Protection: N/A
Other Protective Equipment: Eyewash should be available nearby. Chemical resistant footwear (rubber boots) when using product.

SECTION 9-SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled: Floors will become slippery. Avoid walking in product. Keep unessential personnel away. Mop up or otherwise absorb and hold disposal. Avoid discharge to sewer or open waterways.
Waste Disposal Method: Any method in accordance with local, state and federal laws. Best method is to recycle or reuse for intended purpose. Consult local authorities for disposal in public sewer. Do not dispose of into storm drain, stream, river or to ground. Rinse container thoroughly before discarding in trash.

SECTION 10-REGULATORY INFORMATION

SARA Title III - Section 311/312 -Hazard Categories:
No - Fire Hazard
No - Sudden Release of Pressure Hazard
No - Reactivity Hazard
Yes - Immediate (acute) Health Hazard
No - Delayed (chronic) Health Hazard

Shipping Information:
FOR CONTAINERS > 1 Gallon : Cleaning Compound
FOR 1 GALLON CONTAINERS : Cleaning Compound
FOR CONTAINERS < 1 GALLON : Cleaning Compound

HMIS Hazardous Materials Identification System

Health	1
Flammability	0
Reactivity	0
Personal Protection	A

FOR EMERGENCY MEDICAL OR TRANSPORT INFORMATION: ER# 888-779-1339

This product contains the following toxic chemical(s) subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

CAS#	Chemical Name	Percent by Weight
	None	

This product contains the following chemical(s) which have been established to be either a carcinogen or suspected carcinogen.

CAS#	Chemical Name	Percent by Weight
	None	

SECTION 11-OTHER INFORMATION

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts no responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept no liability for damages or loss incurred from the improper handling and use of this product.